



Private Pilot 150 Maneuvers

	NORMAL TAKEOFF AND CLIMB		CROSSWIND TAKEOFF AND CLIMB
OBJECTIVE	The normal takeoff is one in which the airplane is headed directly into the wind or the wind is very light, and the takeoff surface is firm with no obstructions along the takeoff path, and is of sufficient length to permit the airplane to gradually accelerate to normal climbing speed (V_x).	OBJECTIVE	The crosswind takeoff technique is used to maintain proper ground track while departing a firm or a soft runway. This involves the correct use of aileron/rudder cross control.
ELEMENTS	<ol style="list-style-type: none"> 1. Checklist complete 2. Taxi into takeoff position 3. Full throttle 4. Check engine instruments 5. "Airspeed alive" 6. Rotate at 60 mph or 50 knots 7. Hold approximately 5° nose up 8. Accelerate to and climb out at V_Y 9. At 1000' AGL landing light off 	ELEMENTS	<ol style="list-style-type: none"> 1. Note wind direction and speed 2. Checklist complete 3. Taxi into takeoff position 4. Deflect ailerons into wind – use rudder as required for directional control 5. Full throttle 6. Check engine instruments 7. "Airspeed alive" 8. As speed builds reduce aileron and vary rudder inputs to maintain proper directional control 9. Rotate at 60 mph or 50 knots 10. Hold approximately 5° nose up 11. Accelerate to and climb out at V_x

	SHORT-FIELD TAKEOFF AND MAX PERFORMANCE CLIMB		SOFT-FIELD TAKEOFF AND CLIMB
OBJECTIVE	Taking off and climbing from fields where the takeoff area is restricted by obstructions requires that the pilot operate the airplane at the limit of its takeoff capabilities. The pilot must use all available runway, correctly configure the airplane, develop maximum available horsepower before brake release, rotate at the correct speed, climb at V_x to clear the obstacle, accelerate to V_y , then cycle gear up.	OBJECTIVE	Takeoffs and climbs from soft fields require the use of the operational techniques for getting the airplane airborne as quickly as possible to eliminate drag caused by tall grass, soft sand, mud, snow, etc., and may or may not require climbing over an obstacle. These same techniques are also useful on a rough field where it is advisable to get the airplane off the ground as soon as possible to avoid damaging the landing gear.
OBJECTIVE	<ol style="list-style-type: none"> 1. Before Takeoff Checklist complete (flaps 10°) 2. Taxi into takeoff position (use all available runway) 3. Hold brakes 4. Full throttle 5. Check engine instruments 6. Release brakes after 3 seconds 7. "Airspeed alive" 8. Rotate to lift off at 60 mph or 50 knots 9. Maintain V_x, attitude and airspeed until obstacle cleared or 100 ft above ground 10. Flaps up at or after 100' AGL, positive rate 11. Accelerate to V_y 	ELEMENTS	<ol style="list-style-type: none"> 1. Before Takeoff Checklist complete (flaps 10°) 2. Taxi into position with a smooth turn while maintaining full aft elevator 3. Apply full throttle without stopping aircraft 4. Reduce backpressure as aircraft accelerates to keep nose wheel just clear of the ground 5. Lift off at lowest possible airspeed 6. Maintain aircraft in ground effect until reaching V_Y or V_x 7. Pitch to V_Y attitude (approximately 5°) 8. Flaps up at 100' AGL, positive rate <p><i>Note: Soft field takeoff with an obstacle – accelerate in ground effect to V_x attitude and airspeed until obstacle is cleared</i></p>

	NORMAL APPROACH AND LANDING		CROSSWIND APPROACH AND LANDING
OBJECTIVE	This type of approach and landing involves the use of techniques for what is considered a normal situation; that is, when engine power is available, the wind is light or the final approach is made directly into the wind, the final approach path has no obstacles, and the landing surface is firm and of ample length to gradually bring the airplane to a stop.	OBJECTIVE	Many runways or landing areas are such that landings must be made while the wind is blowing across rather than parallel to the landing direction. Therefore, all pilots should be prepared to cope with these situations when they arise. The same basic principles and factors involved in normal, soft, or maximum performance approach and landing apply to crosswind approach and landings. Only the additional techniques required for correcting wind drift are discussed here.
ELEMENTS	<ol style="list-style-type: none"> 1. Approach checklist completed before entering downwind 2. Slow to 2300-2400 RPM on downwind 3. Midfield, perform before landing checklist 4. Abeam threshold, carb heat on, 1700 RPM, 10° flaps, begin descent at 85 mph (75 knots) 5. At 45° point, turn base, flaps 20°, pitch for 75 mph (65 knots) 6. On final, flaps 30° (optional), 65-70 mph (60-65 knots) 7. Adjust pitch and power to maintain 3° GP so as to be stabilized no lower than 400' AGL 8. Maintain aiming point with pitch/power corrections until approaching round out 9. Reduce power to idle once runway is made 10. Flare airplane so that main gear contacts the runway first 11. Maintain directional control and lower nose wheel before braking 	ELEMENTS	<ol style="list-style-type: none"> 1. Establish appropriate approach configuration (normal, soft field, short-field) 2. Maintain alignment with centerline using crab into wind 3. Lower upwind wing into the wind 4. Simultaneously apply opposite rudder to maintain runway centerline 5. Maintain drift control with aileron 6. Maintain directional control with rudder 7. Flare as normal 8. Optimally, land with upwind main gear touching first

	Emergency Descents		GO-AROUND/REJECTED LANDING
Objective	An emergency descent is a maneuver for descending as rapidly as possible within the structural limitations of the airplane to a lower altitude or to the ground for an emergency landing. The need for this maneuver may result from an uncontrollable fire, a sudden loss of cabin pressurization, or any other situation demanding an immediate and rapid descent.	OBJECTIVE	Regardless of the height above the ground at which it is begun, a safe go-around may be accomplished if an early decision is made, a sound plan is followed, and the procedure is performed properly.
Elements	<ol style="list-style-type: none"> 1. Clearing turns 2. Choose location at which if necessary, emergency landing can be made 3. Carb heat-on 4. Power to idle 5. Set flaps to desired setting (0-20 degrees) 6. Use 30-45 degrees bank throughout the turn(s) to maintain positive load 7. Pitch for airspeed not to exceed maximum flap speed (100 mph or 87 knots) or maneuvering speed (109 mph or 95 knots) 8. Level out 50 ft. above desired <p><i>Note: If multiple turns are made, smoothly increase power on each upwind turn to prevent excessive cooling in the engine altitude</i></p>	ELEMENTS	<ol style="list-style-type: none"> 1. Full throttle 2. Pitch up for and accelerate to VY 3. Reduce flaps to 20° if using 30° immediately 4. Reduce control force by trimming nose down 6. Retract remaining flaps once positive rate of climb is made 7. Pitch to approximately 5° nose up 8. Continue with Normal Takeoff Profile <p><i>Note: Steps 1, 2 and 3 are completed simultaneously</i></p>

	SHORT-FIELD APPROACH AND LANDING		SOFT-FIELD APPROACH AND LANDING
OBJECTIVE	This short field operation requires the use of a procedures and techniques for the approach and landing at fields which have a relatively short landing area or where an approach must be made over obstacles which limits the available landing area.	OBJECTIVE	The approach for a soft field is similar to a normal or short field approach depending on field selection. The major difference between the techniques is that during the soft field landing, the airplane is held 1 to 2 feet off the surface as long as possible to dissipate the forward speed to touch down at the minimum forward speed and at the minimum rate of descent.
ELEMENTS	<ol style="list-style-type: none"> 1. Specify touchdown point on downwind 2. Normal pattern 3. Flaps 30° for absolute minimum landing distance 4. Stabilize final descent at 65 mph (60 knots) no lower than 400' AGL 5. Maintain aiming point with pitch/power corrections until approaching round out 6. Reduce throttle slowly and touchdown no more than 200 ft past aiming point 7. Maintain directional control and lower nose wheel before braking 8. Retract flaps to 0° and apply brakes (simulate maximum braking for training) <p><i>Note: Flaps down for max aerodynamic braking on contaminated surfaces</i></p>	ELEMENTS	<ol style="list-style-type: none"> 1. Specify touchdown point on downwind if required 2. Normal pattern 3. Adjust pitch and power to maintain 3° GP so as to be stabilized no lower than 400' AGL 4. Maintain aiming point with pitch/power corrections until approaching round out 5. During landing flare adjust pitch/power for minimum sink rate 6. Touchdown at slowest possible airspeed with nose-high pitch attitude 7. Lower nose gently to surface and taxi clear of runway with full aft elevator

	POWER-ON STALL		POWER-OFF STALL
OBJECTIVE	Power-on stall recoveries are practiced from straight climbs, and climbing turns with no more than 20° of bank, to simulate an accidental stall occurring during takeoffs and departure climbs.	OBJECTIVE	The practice of power-off stalls is usually performed with normal landing approach conditions in simulation of an accidental stall occurring during landing approaches.
ELEMENTS	<ol style="list-style-type: none"> 1. Clearing turns 2. Perform the maneuver no lower than 1,500' 3. Carb heat on 4. Set power to 1500 RPM 5. Flaps 10° (if specified) 6. Maintain level flight and reduce airspeed to 60 mph (50 knots) 7. Carb heat off 8. Full power 9. Coordinate with rudder pressure 10. Set a nose-high pitch attitude that will allow the airspeed to decrease slowly and evenly (not abrupt) 11. Recognize and announce symptoms of approaching stall 12. Maintain wings level, ball centered 13. Stall the airplane <p>RECOVER-</p> <ol style="list-style-type: none"> 14. Release backpressure and slowly lower nose to horizon (minimal altitude loss, NONE is ideal) and apply rudder opposite to wing drop (if required) 15. As airspeed increases, pitch for V_x or V_y and establish a positive rate of climb 16. Level off and recover to cruise 	ELEMENTS	<ol style="list-style-type: none"> 1. Clearing turns 2. Perform the maneuver no lower than 1,500' 3. Carb heat on 4. Set power to 1500 RPM 5. Maintain altitude while airspeed decreases 6. Slowly lower flaps to 20° 7. Begin stabilized descent at 65 mph (60 knots) 8. Level off, power to idle and pitch up to flare 9. As airspeed decreases, recognize and announce symptoms of approaching stall 10. Stall the airplane <p>RECOVER-</p> <ol style="list-style-type: none"> 11. Carb heat on 12. Full power 13. Reduce pitch to horizon (minimal altitude loss, NONE is ideal) 13. Flaps 10° 14. As airspeed increases, retract remaining flaps 15. Establish climb attitude at V_x or V_y 16. Level off and recover to cruise

	SLOW FLIGHT		STEEP TURNS
OBJECTIVE	To develop pilots sense of feel and ability to use the controls correctly, and to improve proficiency in performing maneuvers in which very low airspeeds are required.	OBJECTIVE	This maneuver consists of a turn in either direction using a bank steep enough to cause an over banking tendency during which maximum turning performance is attained and relatively high load factor imposed.
ELEMENTS	<ol style="list-style-type: none"> 1. Clearing turns 2. Perform the maneuver no lower than 1,500' AGL 3. Carb heat on 4. Reduce power to 1500 RPM 5. Apply back pressure on the elevator to reduce airspeed and maintain altitude, TRIM CONSTANTLY 6. Slowly lower flaps to 20° 7. At 60 mph, add power to ≈2000 RPM (carb heat off above 2000 RPM) to maintain altitude 8. Use pitch attitude to control airspeed 9. Maintain directional control with outside visual references 10. Practice gentle climbs, descents, and turns at constant airspeed and level attitude <p>RECOVER-</p> <ol style="list-style-type: none"> 11. Full power 12. Reduce the angle of attack by lowering the nose and maintain altitude 13. Flaps 10° 14. Retract remaining flaps as airspeed increases and return to cruise 	ELEMENTS	<ol style="list-style-type: none"> 1. Clearing turns 2. Reduce throttle to 2400 RPM to obtain less than 109 mph (95 knots) 3. Establish bank of 45° 4. Adjust pitch, bank and power as necessary to maintain altitude and airspeed 5. After completing a 360° turn, roll wings level for 3-5 seconds, start a steep turn in the opposite direction. Adjust pitch, bank and power as necessary to maintain altitude and airspeed. 6. Time roll out so that wings reach level flight on entry heading (1/2 bank angle lead-out)

	S-TURNS ACROSS A ROAD		TURNS AROUND A POINT
OBJECTIVE	S-Turns are used to develop pilot's ability to compensate for drift during turns along a selected reference on the ground. The maneuver consists of crossing a road at a 90° angle and beginning a series of 180° turns of equal radius in opposite directions, re-crossing the road at a 90° angle, just as each 180° turn is completed.	OBJECTIVE	The turns around a point is a proficiency maneuver used to help the pilot develop the ability to control the aircraft while dividing attention between flight path and traffic, while maintaining a constant radius around a reference point and using an angle of bank no greater than 45°. Drift control must be maintained throughout the entire maneuver.
ELEMENTS	<ol style="list-style-type: none"> 1. Clearing turns 2. Establish 109 mph (95 knots) at 2400 RPM 3. Select a road where a safe landing can be made if required, and enter downwind at 1,000' AGL 4. Apply wind drift correction and bank angle to track a constant radius 180° turn back towards the road using up to, but not to exceed 45° of bank 5. At 180° of turn and over road, begin maneuver in opposite direction 6. Depart maneuver on entry heading 	ELEMENTS	<ol style="list-style-type: none"> 1. Clearing turns 2. Establish 109 mph (95 knots) at 2400 RPM 3. Select a ground reference point near an area where an emergency landing can be made. 4. Enter downwind of selected point at 1,000' AGL 5. Maintain constant altitude and radius around point while adjusting bank and drift correction using no more than 45° of bank at the steepest point of the turn 6. Depart maneuver on entry heading